



Axle Capacity

- 2K
- 4.4K
- 6K
- 8K
- 10K Gen Duty
- 12K
- 3.5K
- 5.2K (6K Reg Duty)
- 7K
- 9K
- 10K Heavy Duty
- 15K

Derate Capacity:

Axle Options

- Spindle** Straight 4" Drop 6" Drop
- Lubrication** Grease EZ-Lube Nev-R-Lube Oil
- Camber** Full Half None
- Drop Center** (V-Camber) Yes No
- Beam Finish** Paint Galvanized Powder Coat
- Oversized Tube** LITW MEDW HVYW

Measurements

Hub Face: _____

Spring Center: _____

Hub Options

- Beam Only Idler (No Brakes No flange) Idler Flanged (No Brakes) Electric Self Adjust
- Electric Manual Adjust Duo Servo Hydraulic Hydraulic Free backing Hydraulic Disc
- Single Servo Hydraulic Hydraulic Free Backing Marine Add Parking Brake Air___ ABS

Bolt Pattern _____

2K Idler Hub Diameter (545)

5.5" 5.5 (8"-12" Wheel) 6.5" (12"-15")

Stud Size 1/2" 9/16" 5/8" Coned 5/8" Flanged

Wiring Addon 33" Wire 32" Braided Sleeve Conduit Wire Protector

Spring Options:

- Spring Seat Location** Underslung Overslung Both None
- Spring Seat Option** Adjustable Fixed
- Springs Mounted** Factory Redneck None
- Spring Type** Double Eye Slipper Spring # _____

NOTES:

_____ SERIAL # _____

Quantity Of Axles Being Ordered: _____ **SIGNATURE:** _____

Customer Name: _____ **Phone:** _____

Address: _____ **City:** _____

State: _____ **Zip:** _____ **Email:** _____